

## Taxi Top LED Display Systems



### Key Features:

- High Resolution 5 mm pixel Spacing
- Intensity more than 5500 nit
- Intelligent Power Supply Management
- Quick installation and maintenance
- Multiple control Options
- Made of high quality LEDs
- Lower Power Consumption
- IP65 grade



# Specifications

Pixel Pitch	5mm
LED Type	SMD 2727
Pixel Density	40000 dot/ m <sup>2</sup>
Module Size	160*160mm
Frame Size	1100mm( L) x 410mm(H) X W:164mm(bottom)/ 99mm (top)
Screen Size	960mm*320mm
Screen Resolution	192*64 dot
Brightness	<b>&gt;=5500 nit</b>
Contrast	>8000:1
View Angle	150° (H)/150° (V)
Scan Mode	1/8 scan
Power Supply Input	DC9--24V
<b>Max Consumption</b>	<b>450w</b>
<b>Average Consumption</b>	<b>150w</b>
Frame Frequency	60-85Hz
Fresh frequency	<b>&gt;1920Hz</b>
Optimal Viewing Distance	3--50M
Life Span	100,000 Hours
MTBF	10,000 Hours
Control Method	Asynchronous
Control Mode	3G/4G/WIFI/ Ethenet/ USB
Temperature Operating	-40° ~+75°
Working Humidity	10% - 95%RH
Screen Protection	Waterproof, rust-proof, dust-proof, anti-static, anti-mildew
Power Protection	over-temperature/over-current/ over-voltage protection
Screen Weight	23kg
Package	Honeybox
Package Dimension	1100mm(L) X 500mm(H) X 270mm(W)
Certificates	CE. ROHS